



Female connection

Male connection

Salomon Jetting Parts B.V.  
 Hoeksedijk 109  
 NL-3299 AE Maasdam  
 tel : +31(0)88 126 1900  
 fax : +31(0)88 126 1999  
 e-mail : [info@salomonjettingparts.com](mailto:info@salomonjettingparts.com)  
 web : [www.salomonjettingparts.com](http://www.salomonjettingparts.com)

Spinner type Turbo 1000 Bar (15Kpsi)  
 Rotierdüsen Turbo 1000 Bar  
 Spin jet type Turbo 1000 Bar

Part No. Teile nr. Art. nr.	Type Form type	Dimension mm.+nozzle Abmessung mm.+Düse afmeting mm.+nozzle	Connection Anschluß aansluiting	Flow Rate Wassermenge Opbrengst	P/N end nozzle Teile nr Ende Düse Art.nr. neus nozzle
15-059-001	TN10.516S	Ø 9,5 x 64	5/16"-24MMSM+seal end	1	HPF 1 P/N 15-065-001
15-059-002				2	
15-059-003	TN10.516		5/16"-24MMSM	1	
15-059-004				2	
15-060-001	TN10	Ø 9,5 x 62	1/16"NPTF	1	
15-060-002				2	
15-161-001	TN12	Ø 12,7 x 64	1/8"BSPF	1	HPF 2 P/N 15-065-002
15-161-002				2	
15-061-001		Ø 12,7 x 61	1/8"NPTF	1	
15-061-002				2	
15-062-001	TN16	Ø 16,9 x 61	1/4"NPTF	1	HPF 3 P/N 15-065-004
15-062-002				2	
15-063-001	TN22	Ø 22,2 x 77	3/8"NPTF	1	HPF 4 P/N 15-065-005
15-063-002				2	
15-064-001	TN26	Ø 26,4 x 93	1/2"NPTF	1	HPF 5 P/N 15-065-006
15-064-002				2	

M = Male / AG / Buitendraad

F= Female / IG / Binnendraad

1/16" flow rate = same 5/16"-24male

Size* (NPT)	Flow Rate	Flow (gpm) at specified pressures (psi)**													Flow (lpm) at specified pressures (bar)**									
		3,000	4,000	5,000	6,000	7,000	8,000	9,000	10,000	11,000	12,000	13,000	14,000	15,000	200	300	400	500	600	700	800	900	1000	
1/16"	1	1.9	2.3	2.6	2.9	3.2	3.5	3.7	4.0	4.2	4.5	4.7	4.9	5.1	7.1	9.1	10.8	12.3	13.8	15.2	16.5	17.8	19.0	
	2	3.0	3.5	4.0	4.4	4.8	5.2	5.6	5.9	6.2	6.6	6.9	7.2	7.5	11.1	13.9	16.3	18.6	20.6	22.6	24.4	26.2	27.9	
1/8"	1	2.6	3.1	3.5	3.9	4.3	4.7	5.0	5.4	5.7	6.0	6.4	6.7	7.0	9.5	12.1	14.5	16.6	18.6	20.5	22.4	24.2	25.9	
	2	5.0	5.9	6.7	7.4	8.0	8.7	9.3	9.9	10.4	11.0	11.5	12.0	12.5	18.7	23.4	27.4	31.1	34.5	37.7	40.7	43.6	46.4	
1/4"	1	2.4	2.9	3.4	3.8	4.2	4.6	5.0	5.4	5.8	6.1	6.5	6.8	7.2	8.9	11.6	14.0	16.3	18.5	20.6	22.6	24.6	26.6	
	2	5.2	6.2	7.0	7.8	8.5	9.2	9.9	10.6	11.2	11.8	12.4	13.0	13.5	19.5	24.5	28.9	33.0	36.8	40.3	43.8	47.0	50.2	
3/8"	1	3.6	4.3	4.9	5.5	6.1	6.6	7.2	7.7	8.2	8.7	9.2	9.6	10.1	13.3	17.1	20.4	23.6	26.5	29.4	32.1	34.8	37.3	
	2	7.0	8.2	9.3	10.4	11.3	12.2	13.1	14.0	14.8	15.5	16.3	17.1	17.8	26.1	32.7	38.5	43.8	48.7	53.3	57.7	61.9	65.9	
1/2"	1	3.0	3.7	4.3	4.9	5.5	6.1	6.6	7.1	7.7	8.2	8.7	9.2	9.7	11.3	14.8	18.2	21.3	24.4	27.3	30.2	33.0	35.8	
	2	6.7	7.9	9.0	10.0	11.0	12.0	12.9	13.7	14.6	15.4	16.2	17.0	17.8	24.7	31.3	37.2	42.6	47.7	52.5	57.1	61.6	65.9	