

## Exitflex high pressure hose grades and specifications

Application	Type Ref	Nom. Bore Metric	Hose I/D mm	Hose O/D mm	Max W.P. bars	Min B.P. bars	Min Bend R mm	Temp Range °C	Inner Tube	Cover	Colour	Braid	
Paint Spray Superior Flexibility Excellent solvent resistance. For all Pneumatic Airless Pumps.	PA 1.2	3	3,2	6.9	350	1400	25	-40 +95	Polyamide	PU	BN	Single HT Carbon Steel Brass plated	
	PA 1.3	4	4.8	9.3	350	1400	35	-40 +95	Polyamide	PU	BN		
	PA 1.4	6	6.4	11.7	325	1300	45	-40 +95	Polyamide	PU	BN		
	PA 1.5	8	8.0	13.9	275	1100	50	-40 +95	Polyamide	PU	BN		
	PA 1.6	10	9.6	15.3	250	1000	60	-40 +95	Polyamide	PU	BN		
		PA 1.8	12	12.7	18.5	200	800	70	-40 +95	Polyamide	PU	BN	Double HT Carbon Steel Brass plated
		PA 2.4	6	6.4	13.9	450	1800	50	-40 +95	Polyamide	PU	BN	
		PA 2.5	8	8.0	15.5	425	1700	60	-40 +95	Polyamide	PU	BN	
		PA 2.6	10	9.6	17.5	425	1700	70	-40 +95	Polyamide	PU	BN	
		PA 2.8	12	12.7	21.5	325	1300	85	-40 +95	Polyamide	PU	BN	
	PA 2.12	20	19.1	30.0	235	940	110	-40 +95	Polyamide	PU	BN	One Steel plus one Textile	
	PAT 2.4	6	6.4	12.9	425	1700	40	-40 +95	Polyamide	PU	BN		
Paint Spray Heavy Duty.	PAT 2.6	10	9.6	17.8	325	1300	50	-40 +95	Polyamide	PU	BN	One Aramide plus one Steel	
	HD 2.4	6	6.4	14.0	675	2700	50	-40 +98	Polyamide	PU	RD		
Paint Spray, Pulsating for Diaphragm Electric Pumps.	HD 2.6	10	9.6	17.5	560	2240	70	-40 +98	Polyamide	PU	RD	Single HT Carbon Steel Brass Plated	
	PR 1.3	4	4.7	9.3	300	1200	35	-40 +80	Polyamide	PU	BK		
Paint Spray, Super Pulsating for Electric Piston Pumps.	PR 1.4	6	6.4	11.7	250	1000	45	-40 +80	Polyamide	PU	BK	DoubleTextile	
	SX 2.3	4	4.7	10.5	275	1100	40	-40 +80	Polyamide	PU	BL		
	SX 2.4	6	6.4	12.8	275	1100	50	-40 +80	Polyamide	PU	BL		
	SX 2.6	10	9.6	17.8	250	1000	80	-40 +80	Polyamide	PU	BL		
	SX 2.8	12	12.7	22.5	250	1000	150	-40 +80	Polyamide	PU	YW		
	KX 2.3	4	4.7	10.4	235	940	40	-40 +95	Polyamide	PU	BL		
Multi Purpose, Moisture cure adhesives 2K Materials etc	KX 2.4	6	6.4	12.3	250	1000	55	-40 +95	Polyamide	PU	BL	Single HT Carbon Steel Brass Plated	
	TC 1.4	6	6.4	11.7	325	1300	45	-40 +120	FEP 140 Teflon	PU	BK		
	TC 1.6	10	9.6	15.3	250	1000	60	-40 +120	FEP 140 Teflon	PU	BK		
Paint Spray, Air Assisted Airless Guns Water Jetting	TC 1.8	12	12.7	18.5	200	800	70	-40 +120	FEP 140 Teflon	PU	BK	Single HT Carbon Steel (Fluid)	
	PMW 1.3	4	4.7	9.0	200	800	35	-40 +95	Polyamide	PU	BK		
	MO 1.4	6	6.4	10.1	7	30	35	-40 +95	PE-E	PU	BN		
Lances, Leader hoses.	DP 1.3	4	4.7	9.0	250	1000	35	-40 +80	PE-E	PU	BZ	Single HT Carbon Steel	
	JET 1.3	4	4.7	10.2	400	1600	45	-40 +80	PE-E	PU	BK	Double HT	
EX 2.4	6	6.4	13.9	450	1800	50	-40 +95	PU		BK			



[www.exitflex.co.uk](http://www.exitflex.co.uk) [info@exitflex.co.uk](mailto:info@exitflex.co.uk)

Switzerland: Telephone +41 (0)-999 92 99 Facsimile +41 (0)-364 25 05

United Kingdom: Telephone +44 (0)-1202 478334 Facsimile +44 (0)-1202 488110

	EX 2.8	12	12.7	21.5	325	1300	85	-40 +80		PU	RD	Carbon Steel
Hydraulics	EX	Available in the same range as PA but with PE-E Polyester Elastomer innertube							PU			

Colour codes: BN (Blue Navy), RD (Red), BK (Black), BL (Blue light), BZ (Bronze), YW (Yellow).

PU = Polyurethane