

# HIGHLY EFFECTIVE SELF-ROTARY WATERBLASTING TOOLS

## GENERAL FEATURES

Scimitar are fundamental tools for waterblasting featuring an efficient speed control system, adjustable thanks to a magnetic brake with easy-rotation of the handle grip. Specially developed for surface treatment, they can be mounted on gun lance or automatized systems.

These lightweight tools are particularly efficient for surface preparation. Scimitar are easy-to-use and easy-to-maintain tools, suitable for many different working areas.

## BENEFITS

- Compact and lightweight
- Stainless steel made
- Wide range of speed by simply rotating the handle grip
- Magnetic brake technology
- Quick replacement of head and four sapphire nozzles
- Titanium head available for low flow applications
- Four-port heads can easily be configured for two-port applications

## SCIMITAR 22K

MAX  
RPM  
1500

MAX  
40 l/min  
10,6 gpm

MAX  
1500 bar  
22 kpsi



| CODE          | MAX FLOW RATE |      | MAX PRESSURE |      | MAX WATER TEMP. |     | ROTATING   | INLET                                 | LENGTH |      | WEIGHT |     |
|---------------|---------------|------|--------------|------|-----------------|-----|------------|---------------------------------------|--------|------|--------|-----|
|               | l/min         | gpm  | bar          | kpsi | °C              | °F  | rpm        |                                       | mm     | inch | kg     | lbs |
| Q231000003580 | 40            | 10,6 | 1500         | 22   | 45              | 140 | 900 - 1500 | Female 1"1/8 UNF for 9/16" Slimline** | 200    | 7,9  | 1,6    | 3,4 |

\*\* Other inlet connections available on request

| HEAD CODE     | NOZZLES CODE           | FLOW RATE   |           | PRESSURE   |           | ROTATING   |
|---------------|------------------------|-------------|-----------|------------|-----------|------------|
|               |                        | l/min       | gpm       | bar        | kpsi      | rpm        |
| Q232310140150 | Q2323100AP260L (4 pcs) | 14,2 - 20,4 | 3,8 - 5,2 | 750 - 1500 | 10,9 - 22 | 900 - 1300 |
|               | Q2323100AP290L (4 pcs) | 18,1 - 25,6 | 4,8 - 6,8 | 750 - 1500 | 10,9 - 22 | 900 - 1400 |
|               | Q2323100AP320L (4 pcs) | 21,7 - 28,6 | 5,7 - 7,6 | 750 - 1500 | 10,9 - 22 | 900 - 1300 |

The specifications are indicative only, company reserves itself the right to make changes without any notice.